CM2C40™ ▢ 32 - 61" AUTOMATED CEILING LIFT

FEATURES

1. **AUTODRIVE™ SYSTEM**
   Ultra fast and quiet travel at over 2" (51 mm) per second with preset viewing position.
2. **TELESCOPING DESIGN**
   Collapses to a stored height of 31" (790 mm) with approximately 40" (101.6 cm) of travel.
3. **MULTIPLE CONTROL OPTIONS**
   Control options include: serial communication, dry contact control, and IR remote (included).
4. **Q-LATCH® MOUNTING SYSTEM**
   Flat panel secures to mount with a latching flag. Easy to connect/disconnect – no tools needed!
5. **CABLE MANAGEMENT**
   Unique cable management system allows cables to move freely with the lift.

WHAT YOU NEED TO KNOW

MULTIPLE CONTROL OPTIONS
AMX/Crestron control compatibility

VOLTAGE OPTIONS
120V or 230V (for 230V order the CM2C40I)

FLEXIBLE INSTALLATION
No width constraints

SHIPS FULLY ASSEMBLED

SPECIFICATIONS

Extension	31-71" (79-180 cm)
Weight Capacity	190 lbs (86.2 kg)
Color	Black

RECOMMENDED ACCESSORIES

PACLR1 ■ Side Speaker Adapter

PACCC1 ■ Center Channel Speaker Adapter

For a complete list of flat panel mount accessories see page 83.

TECHNICAL DRAWINGS